

# TX75XXH series

## 150mA Low Power LDO

<http://www.txsemi.com>

### Features

- Quiescent Current: 4.2uA@12V
- PSRR:60dB@100Hz
- Voltage drop:600mV@100mA
- ESD HBM:8KV
- High input voltage (up to 40V)
- Output voltage accuracy: tolerance  $\pm 2\%$
- Output current:150mA(Typ.)
- TO92,SOT89,SOT89B,SOT23-3,SOT23-5 and SOT23-5B package

### Applications

- Battery-powered equipment
- Communication equipment
- Audio/Video equipment

### General Description

The TX75XXH series is a set of three-terminal low power high voltage regulators implemented in CMOS technology. They allow input voltages as high as 40V. They are available with several fixed output voltages ranging from 1.8V to 5.0V. CMOS technology ensures low voltage drop and low quiescent current. Although designed primarily as fixed voltage regulators, these devices can be used with external components to obtain variable voltages and currents.

### Selection Table

Part No.	Output Voltage	Package	Marking
TX7518Hxx	1.8V	TO92 SOT89 SOT89B SOT23-3 SOT23-5 SOT23-5B	75XX-H#(for TO92) 75XX-H#(for SOT89) 75XX-BH#(for SOT89B) XXH(for SOT23-5&SOT23-3) XXBH(for SOT23-5B)
TX7525Hxx	2.5V		
TX7527Hxx	2.7V		
TX7530Hxx	3.0V		
TX7533Hxx	3.3V		
TX7536Hxx	3.6V		
TX7540Hxx	4.0V		
TX7544Hxx	4.4V		
TX7550Hxx	5.0V		

Note:"XX" stands for output voltages.

TO92 & SOT89 packages will add a "#" mark at the end of the marking.

### Order Information

TX75①②③④⑤


Designator	Symbol	Description
① ②	Integer	Output Voltage(1.8~5.0V)
③	H	Standard
④	T	Package:TO-92
	P	Package:SOT89
	PB	Package:SOT89B
	M	Package:SOT23-3
	M5	Package:SOT23-5
	M5B	Package:SOT23-5B
⑤	G	Halogen Free

# TX75XXH series

## 150mA Low Power LDO


<http://www.txsemi.com>

### Block Diagram




### Pin Assignment


TO92 (Front view)






SOT89 (Top view)



SOT23-5 (Top view)



SOT23-5B (Top view) SOT23-3 (Top view) SOT89B (Top view)



# TX75XXH series

## 150mA Low Power LDO

<http://www.txsemi.com>

### Absolute Maximum Ratings

Supply Voltage .....-0.3V to 40V

Storage Temperature .....-50°C to 125°C

Operating Temperature .....-40°C to 125°C

Note: These are stress ratings only. Stresses exceeding the range specified under “Absolute Maximum Ratings” may cause substantial damage to the device. Functional operation of this device at other conditions beyond those listed in the specification is not implied and prolonged exposure to extreme conditions may affect device reliability.

### Thermal Information

Symbol	Parameter	Package	Max.	Unit
$\theta_{JA}$	Thermal Resistance (Junction to Ambient) (Assume no ambient airflow, no heat sink)	TO92	200	°C/W
		SOT89	200	°C/W
		SOT23-3	500	°C/W
		SOT23-5	500	°C/W
$P_D$	Power Dissipation	TO92	0.50	W
		SOT89	0.50	W
		SOT23-3	0.20	W
		SOT23-5	0.20	W

Note:  $P_D$  is measured at  $T_a = 25^\circ\text{C}$

# TX75XXH series

## 150mA Low Power LDO

<http://www.txsemi.com>

### Electrical Characteristics

The following specifications apply for  $V_{IN} = 12V$ ,  $T_A = 25^\circ C$ ,  $C_{IN} = C_{OUT} = 10\mu F$ , unless specified otherwise.

SYMBOL	ITEMS	CONDITIONS	MIN	TYP	MAX	UNIT
$V_{IN}$	Input Range	$I_{OUT} = 30mA$	$V_{OUT} + 0.3$		40	V
$V_{OUT}$	Output Range	$I_{OUT} = 10mA$	$V_{OUT} \times 0.98$	$V_{OUT}$	$V_{OUT} \times 1.02$	V
$\Delta V_{OUT}$	Output Voltage	$V_{IN} = 12V, I_{OUT} = 10mA$	4.9	5	5.1	V
			3.234	3.3	3.366	
			2.94	3.0	3.06	
$I_Q$	Quiescent Current	$V_{IN} = 7V, I_{OUT} = 0$		4	6	$\mu A$
		$V_{IN} = 24V, I_{OUT} = 0$		4.6	6.7	
		$V_{IN} = 40V, I_{OUT} = 0$		5.4	8.2	
$I_{OUT\_PK}$	Maximum Output Current	$V_{IN} = 12V, R_L = 1\Omega$		190		mA
$V_{DROP}$	Dropout Voltage	$I_{OUT} = 1mA$		200	300	mV
		$I_{OUT} = 100mA$		600	900	
$\Delta V_{LINE}$	Line Regulation	$V_{IN} = 7 \sim 24V, V_{OUT} = 5V, I_{OUT} = 1mA$		0.02	0.03	% / V
		$V_{IN} = 7 \sim 45V, V_{OUT} = 5V, I_{OUT} = 1mA$		0.08	0.1	
$\Delta V_{LOAD}$	Load Regulation	$V_{IN} = 7V, I_{OUT} = 1 \sim 100mA$		19	37	mV
$I_{SHORT}$	Short Current	$V_{OUT}$ Short to GND with $1\Omega$ (1ms pulse), $V_{IN} = 40V$		180		mA
PSRR	Power Supply Rejection Rate	$V_{IN} = 10V,$ $V_{PP} = 0.5V,$ $I_{OUT} = 1mA$	$F = 100Hz$	60		dB
			$F = 1kHz$	50		
			$F = 10kHz$	40		
$e_{NO}$	Output Noise Voltage	10Hz to 100kHz, $C_{OUT} = 10\mu F,$ $I_{OUT} = 10mA$		$\pm 100$		$\mu V_{RMS}$
$T_{SD}$	Thermal Shutdown Protection	$V_{IN} = 12V, I_{OUT} = 1mA$		165		$^\circ C$
$\Delta V_O / \Delta T$	Temperature Coefficient			$\pm 0.5$		mV / $^\circ C$







# TX75XXH series

## 150mA Low Power LDO

<http://www.txsemi.com>

### Typical Performance Characteristics

$C_{IN} = 10\mu F$ ,  $C_{OUT} = 10\mu F$ ,  $T_{OPT} = 25^{\circ}C$ , unless specified otherwise. (Package: SOT89-3L)




# TX75XXH series


## 150mA Low Power LDO

<http://www.txsemi.com>


Output Voltage vs. Output Current




Output Voltage vs. Output Current




PSRR vs. Frequency




Dropout Voltage vs. Output Current



IQ vs. Output current




IQ vs. Temperature



# TX75XXH series

## 150mA Low Power LDO

<http://www.txsemi.com>



### Power ON/OFF



CH1:  $V_{IN}$

CH2:  $V_{OUT}$

$V_{IN}=40V$

$I_{OUT}=1mA$

$V_{OUT}=5V$



### Line Transient


CH1:  $V_{IN}$

CH2:  $V_{OUT}$

$V_{IN}=6V-12V$

$I_{OUT}=1mA$


$V_{OUT}=5V$



$V_{IN}=6V-12V$

$I_{OUT}=10mA$

$V_{OUT}=5V$




# TX75XXH series

## 150mA Low Power LDO

<http://www.txsemi.com>

### Package Information

#### 3-pin TO92 Outline Dimensions




Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	3.300	3.700	0.130	0.146
A1	1.100	1.400	0.043	0.055
b	0.380	0.550	0.015	0.022
c	0.360	0.510	0.014	0.020
D	4.300	4.700	0.169	0.185
D1	3.430		0.135	
E	4.300	4.700	0.169	0.185
e	1.270 TYP.		0.050 TYP.	
e1	2.440	2.640	0.096	0.104
L	14.100	14.500	0.555	0.571
Φ		1.600		0.063
h	0.000	0.380	0.000	0.015



**TX75XXH series**  
**150mA Low Power LDO**

<http://www.txsemi.com>

**3-pin SOT89 Outline Dimensions**




Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	1.400	1.600	0.055	0.063
b	0.320	0.520	0.013	0.020
b1	0.400	0.580	0.016	0.023
c	0.350	0.440	0.014	0.017
D	4.400	4.600	0.173	0.181
D1	1.550 REF.		0.061 REF.	
E	2.300	2.600	0.091	0.102
E1	3.940	4.250	0.155	0.167
e	1.500 TYP.		0.060 TYP.	
e1	3.000 TYP.		0.118 TYP.	
L	0.900	1.200	0.035	0.047

# TX75XXH series

## 150mA Low Power LDO

<http://www.txsemi.com>

### 3-pin SOT23-3 Outline Dimensions




Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.050	1.250	0.041	0.049
A1	0.000	0.100	0.000	0.004
A2	1.050	1.150	0.041	0.045
b	0.300	0.500	0.012	0.020
c	0.100	0.200	0.004	0.008
D	2.820	3.020	0.111	0.119
E	1.500	1.700	0.059	0.067
E1	2.650	2.950	0.104	0.116
e	0.950(BSC)		0.037(BSC)	
e1	1.800	2.000	0.071	0.079
L	0.300	0.600	0.012	0.024
$\theta$	0°	8°	0°	8°

# TX75XXH series

## 150mA Low Power LDO

<http://www.txsemi.com>

### SOT23-5 Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.050	1.250	0.041	0.049
A1	0.000	0.100	0.000	0.004
A2	1.050	1.150	0.041	0.045
b	0.300	0.500	0.012	0.020
c	0.100	0.200	0.004	0.008
D	2.820	3.020	0.111	0.119
E	1.500	1.700	0.059	0.067
E1	2.650	2.950	0.104	0.116
e	0.950(BSC)		0.037(BSC)	
e1	1.800	2.000	0.071	0.079
L	0.300	0.600	0.012	0.024
θ	0°	8°	0°	8°


# TX75XXH series

## 150mA Low Power LDO

<http://www.txsemi.com>

### Product Tape and Reel Specifications


#### 3-pin TO92 Reel Dimensions (Unit: mm)



**TX75XXH series**  
**150mA Low Power LDO**

<http://www.txsemi.com>

**Reel Dimensions**



**SOT89**

Symbol	Description	Dimensions in mm
A	Reel Outer Diameter	180.0±1.0
B	Reel Inner Diameter	62.0±1.5
C	Spindle Hole Diameter	12.75 <sup>+0.15/-0.00</sup>
D	Key Slit Width	1.90±0.15
T1	Space Between Flange	12.4 <sup>+0.2/-0.00</sup>
T2	Reel Thickness	17.0 <sup>+0.0/-0.4</sup>

**SOT23-5**


Symbol	Description	Dimensions in mm
A	Reel Outer Diameter	178.0±1.0
B	Reel Inner Diameter	62.0±1.0
C	Spindle Hole Diameter	13.0±0.2
D	Key Slit Width	2.50±0.25
T1	Space Between Flange	8.4 <sup>+1.5/-0.0</sup>
T2	Reel Thickness	11.4 <sup>+1.5/-0.0</sup>

# TX75XXH series

## 150mA Low Power LDO

<http://www.txsemi.com>

### Carrier Tape Dimensions



TO92

Symbol	Description	Dimensions in mm
I1	Taped Lead Length	(2.5)
P	Component Pitch	12.7±1.0
P <sub>0</sub>	Perforation Pitch	12.7±0.3
P <sub>2</sub>	Component to Perforation (Length Direction)	6.35±0.40
F <sub>1</sub>	Lead Spread	2.5 <sup>+0.4/-0.1</sup>
F <sub>2</sub>	Lead Spread	2.5 <sup>+0.4/-0.1</sup>
Δh	Component Alignment	0.0±0.1
W	Carrier Tape Width	18.0 <sup>+1.0/-0.5</sup>
W <sub>0</sub>	Hold-down Tape Width	6.0±0.5
W <sub>1</sub>	Perforation Position	9.0±0.5
W <sub>2</sub>	Hold-down Tape Position	(0.5)
H <sub>0</sub>	Lead Clinch Height	16.0±0.5
H <sub>1</sub>	Component Height	Less than 24.7
D <sub>0</sub>	Perforation Diameter	4.0±0.2
t	Taped Lead Thickness	0.7±0.2
H	Component Base Height	19.0±0.5

Note: Thickness less than 0.38\_0.05mm~0.5mm

P0 Accumulated pitch tolerance: \_1mm/20itches.


( ) Bracketed figures are for consultation only

# TX75XXH series

## 150mA Low Power LDO

<http://www.txsemi.com>

### Carrier Tape Dimensions



SOT89

Symbol	Description	Dimensions in mm
W	Carrier Tape Width	12.0 <sup>+0.3/-0.1</sup>
P	Cavity Pitch	8.0±0.1
E	Perforation Position	1.75±0.10
F	Cavity to Perforation (Width Direction)	5.50±0.05
D	Perforation Diameter	1.5 <sup>+0.1/-0.0</sup>
D1	Cavity Hole Diameter	1.5 <sup>+0.1/-0.0</sup>
P0	Perforation Pitch	4.0±0.1
P1	Cavity to Perforation (Length Direction)	2.0±0.1
A0	Cavity Length	4.8±0.1
B0	Cavity Width	4.5±0.1
K0	Cavity Depth	1.8±0.1
t	Carrier Tape Thickness	0.300±0.013
C	Cover Tape Width	9.3±0.1

SOT23-5

Symbol	Description	Dimensions in mm
W	Carrier Tape Width	8.0±0.3
P	Cavity Pitch	4.0±0.1
E	Perforation Position	1.75±0.10
F	Cavity to Perforation (Width Direction)	3.50±0.05
D	Perforation Diameter	1.5 <sup>+0.1/-0.0</sup>
D1	Cavity Hole Diameter	1.5 <sup>+0.1/-0.0</sup>
P0	Perforation Pitch	4.0±0.1
P1	Cavity to Perforation (Length Direction)	2.00±0.05
A0	Cavity Length	3.15±0.10
B0	Cavity Width	3.2±0.1
K0	Cavity Depth	1.4±0.1
t	Carrier Tape Thickness	0.20±0.03
C	Cover Tape Width	5.3±0.1

# ***TX75XXH series***

## ***150mA Low Power LDO***

---

<http://www.txsemi.com>

© Shanghai TX Semiconductor Sci.-Tech. Co., Ltd.

TX cannot assume responsibility for use of any circuitry other than circuitry entirely embodied in a TX product. No circuit patent license, copyrights or other intellectual property rights are implied. TX reserves the right to make changes to their products or specifications without notice. Customers are advised to obtain the latest version of relevant information to verify, before placing orders, that information being relied on is current and complete.